

MFX-1330

Multifunction PARTNER

With affordable copy, print, fax and scan capabilities, the MFX-1330 is the ideal workgroup hub.



Key Specifications:

- ✧ 13 pages-per-minute
- ✧ Seamless digital copying
- ✧ Duplex printing (MFX-1330D)
- ✧ Standard color scanning
- ✧ High-speed fax communications
- ✧ OfficeBridge™ Plus connectivity*
- ✧ 80-sheet automatic document feeder
- ✧ Flexible paper capacity

Features & Benefits

13 ppm print engine

- Output printing at speeds up to 13 pages-per-minute increases office productivity

80-sheet automatic document feeder

- Fax, copy and scan large jobs without having to split into multiple sets

Standard color scanning

- High-resolution color scanner offers easy digital transfer of hardcopy photos, charts and various office documents
- TWAIN compliance directly scans images into popular software applications

Duplex printing (MFX-1330D)

- Reduce paper consumption and day-to-day operational costs with duplex print, copy and fax reception capabilities

Flexible paper capacity

- Standard 500-sheet cassette and 50-sheet bypass tray with optional second 500-sheet cassette

Simple network installation

- Print drivers can be installed via server or individual client

Expandable memory

- Standard 8-MB memory can be upgraded to 40-MB, creating sufficient memory storage for large applications

Standard PC printing

- Windows-based GDI printing system produces crisp printouts at 600 dpi

33.6 Kbps modem with JBIG compression

- High-speed modem transfers data at speeds up to 2 seconds per page

OfficeBridge Plus functionality*

The OfficeBridge Plus digital connectivity solution affordably expands the capabilities of the MFX-1330 with the following:

- Network printing
- Desktop faxing
- Scan to e-mail
- Internet faxing
- Network scanning
- DHCP compliance

OfficeBridge Plus also offers inbound fax routing, programming of autodialer numbers directly from the PC and other powerful features – all through an intuitive, browser-based interface.



Intuitive control panel

- Two-line LCD provides clear instruction and operational guidance
- Program keys allow for one-touch initiation of complex fax/copy commands

CONFIGURATIONS – MFX-1330

Model	MFX-1330	MFX-1330 with OfficeBridge Plus
Copier	Yes	Yes
Fax Machine	Yes	Yes
Internet Fax	Optional	Yes
Network/PC Fax	Optional	Yes
Network Print/Scan	Optional	Yes
PC Print/Scan	Yes	Yes
Dual Lines	Optional	Optional
Scan to e-mail	Optional	Yes

SPECIFICATIONS – MFX-1330

GENERAL		OS Support	Win 98SE/Me/NT4.0/2000/XP/Server 2003	Confirmation Report	Yes
Classifications	Segment 1	Alignment	Left corner	Selectable TTI	3
Recording Method	LED	Duplex Print Speed	5 ppm	Max. Scan Width	8.2"
Print Speed	13 ppm	FAX		COPY	
Macro Program Keys	7	Modem Speed	33.6 Kbps	Number of Copies	1-99
Document Feeder	80 sheets	Max. Compression	JBIG	Warm-Up Time	23 seconds
Standard Paper Capacity	550 sheets	Max. Tx Speed	2 spp	FCOT	12 seconds
Max. Paper Capacity	1,050 sheets	Default Scan Speed	1.8 spp	Platen Glass (FBS)	Legal-sized
Cassette Paper Weight	20-24 lb.	Std. Document Mem.	8 MB	Reduction/Enlargement	FBS – 25-400%, ADF – 25-100%
Duplex Printing	1:2	Max. Document Mem.	40 MB	Max. Resolution	600 x 600 dpi
Duplex Scan	Manual	Document Mem. Back-up	72 hours	Grayscale	256 levels
Jam Access	Side cover	One-Touch Locations	40	Default Scan Speed	2.7 spp
Display	2-line LCD	Speed Dial Locations	160	Image Combination	Yes
Department Codes	100	Broadcasting	230 locations	Max. Scanning Width	8.5"
Dimensions (H x W x D)	17.5" x 20.4" x 17.7"	Group Dialing	32 groups	Copy Reservation	Yes
Weight	45.8 lbs.	Cover Page Insertion	Yes	Electronic Sorting	Yes
Toner Yield	5,000 @ 6%	Out-of-Paper Reception	250 jobs	SCAN	
Drum Yield	20,000	Block Junk Fax	50 locations	Resolution	600 x 600 dpi
QuadAccess™	Yes	Security Reception	Yes	Grayscale	256 levels
PRINT		Fax Forwarding	Yes	Interface	USB 2.0
Resolution	600 dpi	Batch Transmission	5 locations	TWAIN Compliant	Yes
Type	Standard GDI, Optional PCL 6	F-Code Compliant	20 boxes	Scan Boxes	20
Interface	Standard USB 2.0	Dual Line	Optional	Default Color Scan Speed	12.88 spp
Ethernet	10/100BaseT, RJ-45 connection	Error Correction Mode	Yes	Default Monochrome Scan Speed	3.7 spp
Network Protocol	TCP/IP	Automatic Redial	2-15 attempts		

*OfficeBridge Plus available second quarter 2005.



As an ENERGY STAR® partner, Muratec America, Inc. has determined that these products meet the ENERGY STAR® guidelines for energy efficiency. Muratec, the Muratec logo and all Muratec product and feature names are trademarks of Muratec America, Inc. Energy Star is a registered trademark of the U.S. Environmental Protection Agency.

All specifications subject to change.



Muratec America, Inc.

3301 East Plano Parkway, Suite 100, Plano, Texas 75074

For more information on Muratec products or services, call (469) 429-3300 or visit our web site at www.muratec.com